



Simple and Easy WT4-AXB

4-inch Industrial Label Printer

▶ Watch video




Easy Installation


- Suitable for a variety of industries and applications.
- Compact design to fit any workspace.
- Supports various media types.
- Flexible options to meet your printing needs.
- Multiple emulations for easy integration into existing systems.
- Compatible with 8.0-inch OD label rolls and 450m ribbon rolls.




Compact design




Label size and roll length



Error display



Multilingual support



Wide label path

Easy operation

- UI with color-coded alerts for quick error identification.
- Multilingual UI for a diverse workforce.
- Color coded controls and wide label path for effortless media replacement.

Easy maintenance


- Easy replacement of thermal printhead and platen roller.
- Backed by SATO's global support.
- Software for centralized configuration of printers across the network.



Thermal printhead



Platen roller



Centralized printer management

TECHNICAL INFORMATION WT4-AXB Printer

PRINTING SPECIFICATION				WT4-AXB (203 dpi)	WT4-AXB (300 dpi)
Printing Method				Thermal Transfer	
Print Resolution				8 dots / mm (203 dpi)	12 dots / mm (300 dpi)
Max. Print Area	Width mm (inch)			104mm (4.09")	104mm (4.09")
	Length mm (inch)			996mm (39.33")	996mm (39.33")
Print Speed, mm/sec (ips)				Up to 203.2mm/sec (8 ips)	Up to 152.4mm/sec (6 ips)
CPU				32-bit RISC Microprocesor	
Printer Memory				Flash ROM: 128MB, DRAM: 128MB User Memory: 32MB External USB User Memory: 16GB	
CONSUMABLES SPECIFICATION					
Sensor Type				Adjustable I-Mark Sensor (Reflective) /Label Gap Sensor (Transmissive), Label Taken sensor, Head Open sensor, Ribbon Out Sensor	
Media Type				Roll or fan-fold die cut labels, Plain paper face stock, Continuous stock, Tag, Ticket	
Media Thickness				0.08 – 0.19mm (0.003" – 0.007")	
Label Shape	Wind Direction			Face-in / Face out	
	Diameter			Roll Max. outside diameter: Ø 203.2mm (8"), Core diameter: 76mm /38mm (3" / 1.5")	
Label Size	Continuous	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")
		Length	6 – 2497mm (0.24" – 98.3")		6 – 1497mm (0.24" – 58.9")
	Tear-Off	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")
		Length	22 – 2497mm (0.86" – 98.3")		22 – 1497mm (0.86" – 58.9")
	Cutter	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")
		Length	22 – 2497mm (0.86" – 98.3")		22 – 1497mm (0.86" – 58.9")
	Dispenser	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")
		Length	22 – 397mm (0.86" – 15.6")		22 – 2497mm (0.86" – 98.3")
Ribbon TT Model	Length		Max. 450 metres. Max Diameter 82mm		
	Width		40mm - 110mm (1.57" – 4.33")		
	Core Diameter		25mm (1")		
	Wind Direction		Face-in / Face-out		
FONTS / SYMBOLOGIES					
Internal Fonts Unicode supported	Standard Bitmap		Bitmap Fonts XS, XU, XM, XB, XL, OCR A, OCR B		
	Scaleable fonts		CG Times, CG Triumvirate, SUD-SON, SUD-HEI		
Barcode	1D Barcode		UPC-A/E, JAN/EAN-8/13, Code 39, Code 93, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, MSI, GS1 Databar: Omni, Truncated, Stacked, Stacked Omni, Limited, Expanded, Expanded stacked. UPC Add-on, Postnet, Industrial 2 of 5. Composite: JAN/EAN-8/13, UPC A/E, GS1 Databar, Truncated and Stacked		
	2D Barcode		PDF417 including Micro pdf, MAXI Code, QR Code, GS1 Data Matrix (ECC200), Aztec		
Print Rotation	Character Data / Barcode		0°, 90°, 180°, 270°		
COMMUNICATION INTERFACES					
Interfacing		Standard: USB Type A 2.0 + USB Type B 2.0 + LAN + RS-232 Options: Wireless LAN b/g/n and Bluetooth			
		LAN protocols: ARP, IP, ICMP, UDP, TCP, HTTP, DHCP, Socket, LPR, SNMPv1.2			
Command languages (Printer language emulations)		SBPL SATO Barcode Printer Language, SZPL, SIPL			
OPERATING CHARACTERISTICS					
Power Requirements		Input voltage: AC100V-240V +/- 10% (full range)/ Frequency 50HZ -60Hz +/- 5%			
Environment	Operating	4 – 40°C / 30 – 80% RH (without condensation)			
	Storage	-20 - 50°C / 15 - 85% RH (without condensation)			
Dimension (W x D x H)		267.7 x 450 x 261mm *(H1 Opcional: 256mm) - 10.54" x 17.71" x 10.30" *(H1 Opcional 10.01")			
Weight		11.4 kg (25.13 lb)			
Indicators, Buttons, Display		3 blue colour LED indicators , 7 x Buttons, 3.5" Color LCD			
MISCELLANEOUS					
Certifications		FCC, UL, CSA, CE, TUV GS, ROHS 2.0 compliant, WEEE compliant			
Self-diagnostics		Error detection functions, Printhead overheat function			
Ease of service		Thermal printhead and Platen roller easily replaced			
OPTIONS & MANAGEMENT					
Accessories		Dispenser, Full cutter, Dual Wireless LAN and Bluetooth Interface			
Printer management		SATO Settings Utility for printer, network & Wireless configuration. SNMPv1.2 USB firmware upgrading			
SATO SUPPORT					
A full range of SATO-manufactured labels, tags and ribbons. SATO Value Support after-sales maintenance					